

-
- Pipeline flow remote control electromagnetic valve - has spreader washer fitted in body cavity under membrane with aperture offset from main lock aperture towards output neck.

L20 ANSWER 114 OF 121 WPINDEX COPYRIGHT 2002 DERWENT INFORMATION LTD
AN 1988-159845 [23] WPINDEX
DNN N1988-121887
DC Q66 X25
IN BABUSHKIN, V A; IVANOV, Y U S; SHCHUCHINS, S K H
PA (SHCH-I) SHCHUCHINSKII S KH
CYC 1
PI SU 1350434 A 19871107 (198823)* 2p
ADT SU 1350434 A SU 1986-4058840 19860214
PRAI SU 1986-4058840 19860214
AN 1988-159845 [23] WPINDEX
AB SU 1350434 A UPAB: 19930923

The valve comprises a body with input and output necks on the same axis, and a main lock in the body cavity fixed on a membrane. The main lock contains the seat of a pulse lock controlled by an electromagnet. There is a spreader washer (6) fitted in the body cavity under the membrane, with an aperture having its axis offset from that of the main lock towards the output neck.

USE/ADVANTAGE - As actuating device in remote control systems of gas and liquid flow in pipelines. More reliable. Bul.41/7.11.87.

1/2